

“Stay Cool, Choose Middleby Celfrost: Setting the Standard in Indian Retail and Hospitality Cooling Solutions”



ISO 9001
ISO 14001



At Middleby Celfrost, we prioritize your business needs with our innovative cooling solutions. Trusted by a diverse array of businesses including hotels, restaurants, supermarkets, cafes, and hospitals, our solutions are tailored to enhance your customer experience while optimizing your operational performance.

Hard Top Chest Freezers from 100 ltrs to 800 ltrs.

Presenting world's finest range of convertible chest freezers/coolers to suit every need, in one, two and three lid variants



Single Door



Double Door



Three Door

Half Freezer / Half Cooler



CFCC-342/360/411/442



Features:

- Unique dual temperature design with separate freezing and cooling chamber
- 2 separate lids for easy access to either chamber



Technical Specification

Product/Model Specification	Hard Top Chest Freezers / Chiller (Convertible)									
	Single Door									
	CF 111	CF 132	CF 155	CF 202	CF 211	CF 232	CF 255	CF 311	CF 332	CF 375
Capacity (litres)	98	91	120	177	197	216	233	283	322	341
Dimension (mm) WxDxH	558x457x838	546x546x812	585x625x896	864x559x813	812x533x863	813x660x838	812x609x914	1092x571x838	1092x660x838	1118x610x914
Temperature Range	-18°C ~ -24°C / 2°C ~ 8°C									
Wheels	No	No	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Refrigerant	R600a	R600a	R134a	R600a	R600a	R600a	R134a	R600a	R290	R290
Rated Load, Wattage	85	55	130	97	90	126	160	140	230	280
No. of Baskets	1	1	1	1	1	1	1	1	1	1
Star Rating	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Product/Model Specification	Hard Top Chest Freezers / Chiller (Convertible)									Hard Top Chest Combination Chiller & Freezer			
	Double Door								Three Door	Double Door			
	CF 355 DD	CF 385 DD	CF 502	CF 505	CF 561	CF 582	CF 595	CF 782	CF 850	CFCC 342	CFCC 360	CFCC 411	CFCC 442
Capacity (litres)	322	341	428	446	465	534	536	674	757	166(C)+130(F)	110(C)+200(F)	220(C)+180(F)	220(C)+185(F)
Dimension (mm) WxDxH	1092x660x864	1105x610x940	1397x660x838	1384x610x940	1657x660x864	1676x660x838	1676x610x940	2100x720x845	2413x648x889	1092x660x838	1200x602x866	1300x640x840	1372x660x838
Temperature Range	-18°C ~ -24°C / 2°C ~ 8°C									-18°C ~ -24°C & 2°C ~ 8°C			
Wheels	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Refrigerant	R290	R290	R290	R290	R290	R290	R290	R290	R290	R290	R290	R600a	R290
Rated Load, Wattage	230	280	230	280	240	255	406	520	300	270	140	142	380
No. of Baskets	1	1	1	1	2	2	1	2	2	1	1	1	1
Star Rating	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Not Applicable			

Specifications, features and colours are subject to change without any notice, due to continuous product development.
Accessories optional, product image are for representation, actual product might vary.

300 mm (±) = 12 inch

Glass Top Freezers



IKG-111



IKG-311/411/511/611



IKG-302/402/502/602



IKG-305/405/505/605



IKG-321C/421C

Curve Glass
with LED inside



IKG-710C (also available in flat Glass)



Canopy optional & can be fixed on all flat/curved/Island glass top freezers to make it a scooping cabinets

- Ultra low energy consumption
- Longer holding
- Fastest cooling
- Special design end to end basket



IL-450/550

Technical Specification

Product/Model Specification	Flat Glass Top Chest Freezers									
	IKG 111	IKG 302	IKG 305	IKG 311	IKG 402	IKG 405	IKG 411	IKG 502	IKG 505	IKG 511
Capacity (litres)	100	210	217	285	313	320	363	416	419	439
Dimension (mm) WxDxH	597x508x813	815x682x775	826x610x838	991x686x838	1105x682x792	1092x610x864	1194x686x864	1395x682x792	1384x610x864	1422x686x838
Temperature Range	-10°C ~ -30°C	-18°C ~ -24°C	-18°C ~ -24°C	-10°C ~ -30°C	-18°C ~ -24°C	-18°C ~ -24°C	-10°C ~ -30°C	-18°C ~ -24°C	-18°C ~ -24°C	-10°C ~ -30°C
Wheels	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Refrigerant	R600a	R290	R290	R290	R290	R290	R290	R290	R290	R290
Rated Load, Wattage	160	300	300	220	325	300	240	285	430	280
No. of Baskets	1+1 [#]	1	2	2+2 [#]	2	3	2+2 [#]	2	4	4+2 [#]
Star Rating	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	-

Product/Model Specification	Flat Glass Top Chest Freezers				Curve Glass Top Chest Freezers			Island Showcase	
	IKG 602	IKG 605	IKG 611	IKG 711	IKG 321C	IKG 421C	IKG 710C	IL-450	IL-550
Capacity (litres)	519	556	524	650	243	391	650	426	528
Dimension (mm) WxDxH	1685x682x792	1676x610x889	1651x686x838	1803x673x838	970x650x850	1300x680x850	1803x673x838	1740x699x914	1890x850x870
Temperature Range	-18°C ~ -24°C	-18°C ~ -24°C	-10°C ~ -30°C	-18°C ~ -24°C	-10°C ~ -30°C	-10°C ~ -30°C	-18°C ~ -24°C	-18°C ~ -22°C	
Wheels	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Refrigerant	R290	R290	R290	R290	R290	R290	R290	R290	R290
Rated Load, Wattage	525	430	300	400	220	240	400	275	310
No. of Baskets	4	4	4+2 [#]	9	3	6	9	4	6
Star Rating	Yes	Yes	-	-	Yes	Yes	-	-	-

Specifications, features and colours are subject to change without any notice, due to continuous product development.
Accessories optional, product image are for representation, actual product might vary.

300 mm (≈) = 12 inch

[#] QDI Baskets

Showcase Freezers



NFG 200G*



NFG 450G*



NFG 1000AG*



NFG 1500G*



BFS-150/250/350

Upright Freezer

Technical Specification

Upright Showcase Freezers	Product / Model Specification								
	Capacity (litres)	Dimension (WxDxH) mm	Temperature Range	Wheels	Lock	Refrigerant	Rated Load, Wattage	No. of Baskets/ Shelves	No. of Lids /Doors
NFG 200G	211	610x610x991	-18°C ~ -22°C*	Yes	Yes	R290	360	2	1
NFG 400C	400	690x600x2025	-18°C ~ -22°C*	Yes	Yes	R290	400	5	1
NFG 450G	450	680x630x2130	-18°C ~ -22°C*	Yes	Yes	R290	1000	4	1
NFG 1000AG	1078	1370x630x2130	-18°C ~ -22°C*	Yes	Yes	R290	1100	5+5	2
NFG 1500G	1657	2057x700x1985	-18°C ~ -22°C*	Yes	Yes	R290	1300	4+4+4	3
BFS 150	150	546x526x1143	-20°C	Adjustable Feet	Yes	R134a / R600a	100	5	1
BFS 250	250	610x610x1494	-20°C		Yes	R134a / R600a	120	8	1
BFS 350	350	610x597x1786	-20°C		Yes	R600a	140	7	1

* Suitable to work at ambient temperature 28°C.

Accessories optional, product image are for representation, actual product might vary.

Counter tops for retail solution



IKG 60



MF 51G



FKG 20C/58C



NFGC 49



CBF 67



FSDCR 108/FSDHR 108



FSDC 58



HAD-40

Hot Air Display from
Lincat
with Independent temperature control for each compartment

Technical Specification

Product/Model Specification	Counter Top Display									Hot Showcase
	IKG 60	CBF 67	FSDC 58	FKG 20C	FKG 58C	NFGC 49	MF 51G	FSDCR 108	FSDHR 108	
Capacity (litres)	60	27	58	20	58	55	50	108	108	NA
Dimension (mm) WxDxH	580x520x490	805x670x360	425x404x830	330x343x584	420x420x790	620x530x680	432x457x483	470x470x850	470x470x850	400x500x845
Temperature Range	-18°C*	-18°C ~ -22°C / 2°C ~ 10°C*	2°C ~ 10°C*			-18°C ~ -22°C*	2°C ~ 10°C*	2°C ~ 10°C*	30°C ~ 90°C	65°C ~ 70°C
Wheels/Legs	NA	Adjustable Feet	Legs	Adjustable Feet		Legs	Legs	Adjustable Feet		Legs
Lock	NA	NA	Yes	Optional		Yes	NA	Optional		NA
Refrigerant	R134a	R600a	R600a	R600a	R600a	R290a	R600a	R600a	NA	NA
Rated Load, Wattage	80	140	180	82	82	100	80	230	1200	2200
No. of Baskets/Shelves	1	8*1/6 GN PAN	2	1	2	2	1	4 (Rotating)	4 (Rotating)	2
No. of Lids/Doors	2	1	1	1	1	1	1	1	1	NA
Digital Controller	-**	Yes	Yes	-	-	Yes	-	Yes	Yes	-

* Suitable to work at ambient temperature 28°C.

**With digital temperature display.

* Suitable to work at ambient temperature 32°C.

Accessories optional, product image are for representation, actual product might vary.



Wide Range of Showcase Coolers



FKG 120



FKG 235



FKG 320



FKG 400



FKG 330



FKG 430



FKG 322/422 Dlx



FKG 350



FKG 450



FKG 520



FKG 610

Technical Specification

Product/Model Specification	Upright Showcase Chiller												
	FKG 120	FKG 125	FKG 235	FKG 320	FKG 322 Dlx	FKG 330	FKG 350	FKG 400	FKG 422 Dlx	FKG 430	FKG 450	FKG 520	FKG 610
Capacity (litres)	120	115	210	285	285	300	310	380	380	400	410	480	580
Dimension (mm) (WxDxH)	559x533x838	470x500x1025	559x559x1270	559x559x1727	545x620x1727	559x559x1651	575x525x1770	584x610x1993	600x665x1877	648x563x1910	575x565x1920	650x615x1995	850x660x2184
Temperature Range	2°C ~ 8°C												
Wheels	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Refrigerant	R600a	R600a	R600	R600	R600	R600a	R600a	R600	R600	R600a	R600a	R600a	R290
Rated Load, Wattage	170	163	180	200	200	206	200	240	240	306	220	260	300
No. of Shelves/Drawer	2	3	4	4	4	4	4	5	5	4	5	5	5
No. of Doors	1	1	1	1	1	1	1	1	1	1	1	1	1

* at ambient of 32°C.

** FKG-1000C top mounted compressor & aluminum door frame.

Accessories optional, product image are for representation, actual product might vary.

300 mm (±) = 12 inch



Wide Range of Showcase Coolers



FKG 620 DD



FKG 820 DD



FKG 1000 SG
(FKG 1000 SGB in Black Colour)



FKG 909 DD/1200 C



FKG 1500 G

Technical Specification

Product/Model Specification	Upright Showcase Chiller						
	FKG 620 DD	FKG 820 DD	FKG 909 DD	FKG 1000 SG	FKG 1000 SGB	FKG 1200 C	FKG 1500 G
Capacity (litres)	610	750	742	1030	1030	1027	1426
Dimension (mm) (WxDxH)	1000x590x2015	1200x590x2015	1041x610x2057	1206x686x2082	1200x710x1940	1220x700x2020	2006x750x2010
Temperature Range	2°C ~ 8°C						
Wheels	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Refrigerant	R290	R290	R290	R290	R290	R290	R290
Rated Load, Wattage	415	425	330	456	456	400	700
No. of Shelves/Drawer	2x4	2x4	2x5	2x5	2x5	2x5	3x5
No. of Doors	2	2	2	2	2	2	3

* at ambient of 32°C.

** FKG-1000C top mounted compressor & aluminum door frame.

Accessories optional, product image are for representation, actual product might vary.

300 mm (±) = 12 inch

Serve Over Counter



Plug-in & Remote

Island Freezers & Coolers



IL-450/550

Technical Specification for Remote Multideck Chiller

IDU Model	RHTS 2500	RHTS 3750
Dimension (WxDxH) in mm	2500 x 865 x 2000	3750 x 865 x 2000
Capacity (Ltr)/Display Area (m2)	1790/6.08	2650/8.65
Temperature Range	+2°C ~ +10°C (at 25°C, 60% RH)	
Legs	Adjustable Feet	
Night Curtain/Shelves Light	Yes	Yes
No of Shelves (Shelves Angle)	4 (0° / 10° / 20°)	
Digital Controller	Yes	Yes
Defrost Drain	Yes	Yes
Automatic Evaporation of drain Water	No (Drain Provision to be provided at site)	
Condensing Unit (ODU)	CCO 127 HA	CCO 217 HA
Input Power IDU/ODU (W)	480/2500	700/3200
Electrical IDU/ODU	220 V / 50 Hz	220 V / 50 Hz & 400 V / 50 Hz
Refrigerant	R 404a	R 404a

Accessories optional, product image are for representation, actual product might vary.

Plug-in Multideck Chiller



HTS 1000 / 1200 / 1500



HTS510



HTS 380

Technical Specification

Product/Model Specification	Island Showcase		Multideck Chillers				
	IL-450	IL-550	HTS 380	HTS 510	HTS 1000	HTS 1200	HTS 1500
Capacity (litres)	426	528	380	220	770	950	1125
Dimension (mm) WxDxH	1740 x 699 x 914	1890 x 850 x 870	1000 x 890 x 1520	680 x 495 x 1745	1060 x 750 x 1978	1260 x 750 x 1978	1560 x 750 x 1978
Temperature Range	-18°C ~ -22°C*	-18°C ~ -22°C*	2°C ~ 10°C#	2°C ~ 10°C#	2°C ~ 10°C#	2°C ~ 10°C#	2°C ~ 10°C#
Wheels	Yes	Yes	Yes	Adjustable Feet			
Lock	Yes	Yes	NA	NA	NA	NA	NA
Refrigerant	R290	R290	R290	R404a	R404a	R404a	R404a
Rated Load, Wattage	275	310	1300	830	1100	1100	1650
No. of Baskets/Shelves	4	6	3	3	4	4	4
No. of Lids/Doors	2	2	NA	NA	NA	NA	NA
Night Curtain	NA	NA	Yes	Yes	Yes	Yes	Yes

* Suitable to work at ambient temperature 28°C

Suitable to work at ambient temperature 32°C

Accessories optional, product image are for representation, actual product might vary.

Remote Multideck Chiller



Display-cum Storage Coldroom



Close door option available in Chiller & Freezer

Quenching Thirsts & Refreshing every Moments:

Celfrost Water Coolers -

Pure Refreshment, Every Pour, Every Sip.

Celfrost



Technical Specifications

Model	S.Dlx. 20/20	SDLX 21-21	S.Dlx. 20/40	SDLX 21-41	S.Dlx. 40/80	SDLX 41-81	S.Dlx. 60/120	SDLX 61-121	S.Dlx. 150/150	SDLX 151-151	S.Dlx. 200/400	SDLX 201-201	S.Dlx. 400/400
Cooling Capacity	20	20	20	20	40	40	60	60	150	150	200	200	400
At 10°C temperature drop (Ltr/hr)	35	35	35	35	65	65	100	100	245	235	400	270	520
Glasses/hr at rated condition (Ltr/hr)	100	100	100	100	200	200	300	300	750	750	1000	800	1000
Storage Capacity (Ltr)	20	20	40	40	80	80	120	120	150	150	400	200	400
No. of Faucets - cold water	1	1	1	1	2	2	2	2	2	3	4	3	4
Faucets Material	Brass (Cr Plated)												
Dimensions (mm)	370x370x1000	381x381x1092	370x370x1185	475x475x1236	559x457x1210	648x457x1219	700x540x1160	737x559x1168	660x508x1232	860x755x1236	1160x700x1400	1090x755x1236	1190x720 x1400
Compressor / Make	Emerson 419 / LG-MA 53	Tecumseh 1340 / Equivalent	Emerson 419 / LG-MA 53	Tecumseh 1340 / Equivalent	Emerson 443, 444 / LG-MA 88	Tecumseh 1365 / Equivalent	Emerson 461	Emerson 461 / Equivalent	Emerson 513	Emerson 511 / Equivalent	Emerson 513 / CR 22	Emerson 513 / Equivalent	Emerson / CR 30
Compressor / Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R-22	R-22	R-22	R134a
Power (Watts)	390	300	390	300	450	450	775	750	1550	1070	2000	1340	2350
Net Weight (Kgs.)	33	30	35	34	48	49	55	61	70	86	90	97	125
Legs	Nylon												
Water inlet hose pipe	Provided (Food Grade)												
Drain Pipe	Provided												
Over Flow Pipe	Provided												
Motor Make	Micro / Marathon (GE Motors) / Hicool / Rexnord / Equivalent												

Note:

- All Models are suitable for operation on 230V / 1Ph / 50Hz AC Supply.
- Specification and features are subject to change without notice, due to continuous product development.
- Accessories optional, product image are for representation, actual product might vary.



Middleby Celfrost Innovations (P) Ltd.

Corp. Office : Unit Nos. SF-713 — 716, 7th Floor, JMD Megapolis, Sohna Road, Sector 48, Gurugram - 122 018, Haryana, India.
Tel. : +91 124 482 8500, Fax : +91 124 427 9663, E-mail : corp@middlebycelfrost.com, Web : www.middlebycelfrost.com

Toll Free Customer Service No.: 1800-102-1980 • service.india@middlebycelfrost.com

For sales related queries :-

Call: +91 124 4828500 • Email: sales@middlebycelfrost.com